

Plastic square shape inductive sensors **LE09** series


Features

- ◆ Non contact detection, safe and reliable;
- ◆ ASIC design;
- ◆ Perfect choice for metallic targets detection;




Part number

NPN NO	LE09SN25DNO	PNP NO	LE09SN25DPO
NPN NC	LE09SN25DNC	PNP NC	LE09SN25DPC

Technical specifications

Mounting	Non-flush	Current consumption	≤10mA
Rated distance [Sn]	2.5mm	Circuit protection	Short-circuit, overload and reverse polarity
Assured distance [Sa]	0...2mm	Output indicator	Red LED
Dimensions	8 * 8 * 23 mm	Ambient temperature	-25°C...70°C
Output	NO/NC(depends on part number)	Ambient humidity	35-95%RH
Supply voltage	10...30 VDC	Switching frequency [F]	1000 Hz
Standard target	Fe 8*8*1t	Voltage withstand	1000V/AC 50/60Hz 60s
Switch-point drifts [%/Sr]	≤ ± 10%	Insulation resistance	≥50MΩ(500VDC)
Hysteresis range [%/Sr]	1...20%	Vibration resistance	10...50Hz (1.5mm)
Repeat accuracy [R]	≤ 3%	Degree of protection	IP67
Load current	≤ 100mA	Housing material	PC
Residual voltage	≤ 2.5V	Connection type	2m PVC cable

Dimensions



Wiring diagram

